

Dräger PAS Colt

Combining versatility, ease of use and the latest in breathing apparatus design, Dräger's PAS Colt is among the most technologically advanced short duration and emergency escape units available.



The very latest harness design and materials, accompanied by smaller, lightweight cylinders, make wearing this set easier and more comfortable. The versatility allows it to be used effectively in applications and environments ranging from chemical spills and decontamination operations to routine maintenance tasks.

The Dräger PAS Colt is a hip-mounted unit with a distinctive, sophisticated harness design which retains its form, making it easy for the wearer to don the apparatus simply and quickly.

The procedure for donning the apparatus is evident at first glance, even to the inexperienced user, equipped, as an option, with a unique 'drop down' feature, whereby the cylinder can be un-clipped from the waistbelt, makes the Dräger PAS Colt ideal for use in confined space entry applications.

The harness has been constructed using an anti-static material inert to chemicals and oil, and impervious to most acids and alkalis. Benefiting from a high resistance to abrasion and heat, this new harness meets the requirements of EN137 heat and flame resistant and is machine washable.

This material was chosen because of its flexibility and ability to retain its form and shape, in a wide range of temperatures. Its durability, ease of cleaning, resilience and strength means it is ideal for use in extreme conditions. The technology used in the development of this unit is inherited from Dräger's advanced PSS® range of breathing apparatus, designed for professional fire fighters. The buckles used are designed to be easily located, even when wearing gloves, for quick adjustment, but follow the contours of the unit to reduce the risk of snagging.



ST-3557-2003

Dräger PAS Colt
A compact, hip-mounted life saver.

Depending on the requirements of the operation, this unit has been fully approved for use in applications requiring either; short duration entry units, airline emergency escape breathing apparatus or dual function.

Short Duration Entry Unit (EN137)

Gauge and high pressure whistle warning units, sounding at 55 bar, are located at the waist to enable easy and regular checking during operation.

Airline Emergency Escape (EN402) or Escape unit with Airline belt manifold (EN402 / EN139)

When used independently or in conjunction with Dräger's PAS AirPack 1 or 2 Airline systems, for airline emergency escape breathing apparatus (EN402), or dual function (EN139). The pressure indicator is integrated into the cylinder valve to allow for easy periodical inspection.



ORDER INFORMATION

Dräger PAS Colt

Escape unit - Approved to EN402

Carrying system to suit a 2 Litre 200 bar cylinder	33 52 761
Compatible 2 Litre 200 bar cylinder (Aluminum)	33 52 689
Carrying system to suit a 3 Litre 200 bar cylinder	33 52 744
Compatible 3 Litre 200 bar cylinder (Steel)	33 52 690
Carrying system to suit a 2 Litre 300 bar cylinder	33 52 778
Compatible 2 Litre 300 bar cylinder (Carbon Composite)	33 52 688

Escape unit with Airline Belt Manifold - Approved to EN402 / EN139

Carrying system to suit a 2 Litre 200 bar cylinder	33 52 626
Compatible 2 Litre 200 bar cylinder (Aluminum)	33 52 689
Carrying system to suit a 3 Litre 200 bar cylinder	33 52 413
Compatible 3 Litre 200 bar cylinder (Steel)	33 52 690
Carrying system to suit a 2 Litre 300 bar cylinder	33 52 627
Compatible 2 Litre 300 bar cylinder (Carbon Composite)	33 52 688

Short Duration Entry Unit - Approved to EN137

Carrying system to suit a 3 Litre 200 bar cylinder	33 52 634
Compatible 3 Litre 200 bar cylinder (Steel)	33 52 684
Carrying system to suit a 3 Litre 300 bar cylinder	33 52 920
Compatible 3 Litre 300 bar cylinder (Carbon Composite)	33 52 682
Carrying system to suit a 2 Litre 300 bar cylinder	33 52 635
Compatible 2 Litre 300 bar cylinder (Carbon Composite)	33 52 683

Airline Belt Manifold - Approved to EN139

Airline Belt Manifold with whistle warning unit / fixed plus Lung Demand Valve	33 52 942
Airline Belt Manifold without whistle warning unit / fixed plus Lung Demand Valve	33 52 941
Airline Belt Manifold with whistle warning unit / with Quick Release Coupling (product requires a Lung Demand Valve)	33 52 948
Airline Belt Manifold without whistle warning unit / with Quick Release Coupling (product requires a Lung Demand Valve)	33 52 947

Accessories

Leg Strap	33 53 281
Backpack carry bag	33 54 491
Airline Belt Manifold	33 52 564
Airline Belt Manifold complete with whistle warning unit	33 52 565
Plus Lung Demand Valve	33 38 700
PAS Automatic Switchover Valve for the PAS Colt (for safe Airline operations)	33 54 140

Cylinder and valve assemblies

2 Litre 200 bar (Aluminum) cylinder and valve assembly for escape use	33 52 689
3 Litre 200 bar (Steel) cylinder and valve assembly for escape use	33 52 690
2 Litre 300 bar (Carbon Composite) cylinder and valve assembly for escape use	33 52 688
3 Litre 300 bar (Carbon Composite) cylinder and valve assembly for escape use	33 52 687
3 Litre 200 bar (Steel) cylinder and valve for short duration entry use	33 52 684
2 Litre 300 bar (Carbon Composite) cylinder and valve for short duration entry use	33 52 683
3 Litre 300 bar (Carbon Composite) cylinder and valve for short duration entry use	33 52 682

TECHNICAL DATA

Standard	EN402	EN137
Size (H x W x D) - Min (mm)	790 x 500 x 70	550 x 500 x 70
Size (H x W x D) - Max (mm)	950 x 500 x 70	640 x 500 x 70
Weight (kg)	2	2.5
Input Pressure Cylinder (bar)	200 or 300	200 or 300
Input Pressure Airline (bar)	6 - 9	6 - 9
Nominal 1st stage output Pressure (bar)	7	7
1st stage output Flow (l/min)	>600	>600
LDV Output flow (l/min)	>400	>400
Whistle activation pressure (bar)	*4 - 5	55 - 60
Whistle Sound Level (dBA)	*>90	>90
Whistle Frequency Range (Hz)	*2000 - 4000	2000 - 4000
Operating Temperature Range (°C)	-32 to +70	-32 to +70

*Whistle for EN402 unit located as an option on the Airline belt manifold.

HEADQUARTERS:

Dräger Safety AG & Co. KGaA
Revalstrasse 1
23560 Lübeck, Germany

www.draeger.com

SUBSIDIARIES:

AUSTRALIA

Draeger Safety Pacific Pty. Ltd.
Axess Corporate Park
Unit 99, 45 Gilby Road
Mt. Waverley. Vic 3149
Tel +61 3 92 65 50 00
Fax +61 3 92 65 50 95

CANADA

Draeger Canada Ltd.
7555 Danbro Crescent
Mississauga,
Ontario L5N 6P9
Tel +1 905 821 89 88
Fax +1 905 821 25 65

P. R. CHINA

Beijing Fortune Draeger
Safety Equipment Co., Ltd.
Yu An Lu A 22, B Area
Beijing Tianzhu Airport
Industrial Zone
Houshayu Shunyi District
Beijing 101300
Tel +86 10 80 49 80 00
Fax +86 10 80 49 80-05

FRANCE

Dräger Safety France SAS
3c route de la Fédération,
BP 80141
67025 Strasbourg Cedex 1
Tel +33 3 88 40 59 29
Fax +33 3 88 40 76 67

USA

Draeger Safety, Inc.
101 Technology Drive
Pittsburgh, PA 15275
Tel +1 412 787 83 83
Fax +1 412 787 22 07

MEXICO

Draeger Safety S.A. de C.V.
Av. Peñuelas No. 5
Bodega No. 37
Fraccionamiento Industrial
San Pedrito
Querétaro, Qro México
Tel +52 442 246-1113
Fax +52 442 246-1114

NETHERLANDS

Dräger Safety Nederland B.V.
Edisonstraat 53
2700 AH Zoetermeer
Tel +31 79 344 46 66
Fax +31 79 344 47 90

REP. OF SOUTH AFRICA

Dräger South Africa (Pty) Ltd.
P.O.Box 68601
Bryanston 2021
Tel +27 11 465 99 59
Fax +27 11 465 69 53

SINGAPORE

Draeger Safety Asia Pte. Ltd.
67 Ayer Rajah Crescent # 06 03
139950 Singapore
Tel +65 68 72 92 88
Fax +65 67 73 20 33

SPAIN

Draeger Safety Hispania S.A.
Calle Xaudaró 5
28034 Madrid
Tel +34 91 728 34 00
Fax +34 91 729 48 99

UNITED KINGDOM

Draeger Safety UK Ltd.
Blyth Riverside Business Park
Blyth, Northumberland
NE24 4RG
Tel +44 1670 352 891
Fax +44 1670 356 266