

ABM/LB102

Energy absorber
with twin-tail lanyard

EN 355

Ref. no.: BW200/LB102



PARAMETERS

LANYARD

Material:	polyester
Manufacture:	kernmantle lanyard
Diameter:	10,5 mm

ENERGY ABSORBER

Manufacture:	polyamide webbing
Dimensions:	200x32x45 mm

SPECIAL FEATURES



**PERMITTED TO WORK IN
POTENTIALLY EXPLOSIVE AREAS**

DEVICE STANDARD CONFIGURATIONS

NEW CONNECTOR AZ 029

1 2 3



Ref. no. **BW200/LB102/3AZ011**

Energy absorber ABM with lanyard LB 102 and connectors 3 x AZ 011 (galvanized steel, opening 18mm)

2,0 m



Ref. no. **BW200/LB102/AZ002/2AZ029**

Energy absorber ABM with lanyard LB 102 and connectors AZ 002 (galvanized steel, opening 19mm) 2 x AZ 029 (galvanized steel, plastic, opening 50mm)

2,0 m



Ref. no. **BW200/LB102/AZ003/2AZ029**

Energy absorber ABM with lanyard LB 102 and connectors AZ 003 (aluminium, opening 20mm) 2 x AZ 029 (galvanized steel, plastic, opening 50mm)

2,0 m



Ref. no. **BW200/LB102/AZ002/2AZ025**

Energy absorber ABM with lanyard LB 102 and connectors AZ 002 (galvanized steel, opening 19mm) 2 x AZ 025 (galvanized steel, opening 83mm)

2,0 m



Ref. no. **BW200/LB102/AZ003/2AZ024**

Energy absorber ABM with lanyard LB 102 and connectors AZ 003 (aluminium, opening 20mm) 2 x AZ 024 (aluminium, opening 100mm)

2,0 m

Ref. no. **BW200/LB102**

Energy absorber ABM with lanyard LB 102 WITHOUT CONNECTORS

1,8 m

OTHER DEVICE CONFIGURATIONS ON SPECIAL REQUEST