

AZ 700

Webbing sling

EN 795 TYPE B

Ref. no.: AZ 700

CE

PRODUCT
PRESENTATION

protekt.co/az700



Webbing sling AZ 700 is formed by polyamide webbing 45mm wide. Inner side of the sling has non-slip rubber protective coating. It is suitable for protection of 3 users at a time with device AE 320.

PARAMETERS

Material:	polyester, rubber, galvanized steel
Webbing width:	45 mm
Static strength:	30 kN

DEVICE VERSIONS

DEVICE VERSIONS	LENGTH
AZ 700 090	90 cm
AZ 700 140	140 cm
AZ 700 200	200 cm

SPECIAL FEATURES

Protection of
1 PERSONPERMITTED TO WORK IN
POTENTIALLY EXPLOSIVE AREAS

AZ 410

Connecting lanyard

EN 354, EN 795 TYP B

Ref. no.: AZ 410, AZ 430

CE

PRODUCT
PRESENTATION

protekt.co/az410



Connecting lanyard AZ 410 is a component of fall protection equipment. When combined with an energy absorber (e.g. ABM) forms a connecting and absorbing device. Connecting lanyard is a portable anchor point complying with EN 795/B. Connecting lanyard AZ 430 is a portable anchor point complying with EN 795/B. It is suitable for protection of 3 users at a time with device AE 320. Material: galvanized steel cable, 6.3mm dia, fitted with loops with thimbles at both endings. The middle part of the lanyard is protected by a transparent plastic tube.

PARAMETERS

Material:	steel
Manufacture:	kernmantle rope
Diameter:	6,3 mm

DEVICE VERSIONS

DEVICE VERSIONS	LENGTH
AZ 410	1,0 m
AZ 410	2,0 m
AZ 430	3,0 m
AZ 430	5,0 m
AZ 430	10,0 m

SPECIAL FEATURES

Protection of
1 PERSONPERMITTED TO WORK IN
POTENTIALLY EXPLOSIVE AREAS