

ABM/LB101

Energy absorber with lanyard

EN 355

Ref. no.: **BW200/LB101**



ENERGY ABSORBER TESTED
IN LABORATORY

protekt.co/abmlb101lab



PARAMETERS

LANYARD

Material: polyester
Manufacture: kernmantle lanyard
Diameter: 10,5 mm

ENERGY ABSORBER

Manufacture: polyamide webbing
Dimensions: 200x32x45 mm

SPECIAL FEATURES



PERMITTED TO WORK IN
POTENTIALLY EXPLOSIVE AREAS

DEVICE STANDARD CONFIGURATIONS

N NEW CONNECTOR AZ 029

1

2



Ref. no. **BW200/LB101/2AZ011**

Energy absorber ABM with lanyard LB 101
and connectors 2 x AZ 011 (galvanized steel, opening 18mm)

2,0 m



Ref. no. **BW200/LB101/2AZ002**

Energy absorber ABM with lanyard LB 101
and connectors 2 x AZ 002 (galvanized steel, opening 19mm)

2,0 m



Ref. no. **BW200/LB101/2AZ003**

Energy absorber ABM with lanyard LB 101
and connectors 2 x AZ 003 (aluminium, opening 20mm)

2,0 m



Ref. no. **BW200/LB101/AZ002/AZ029**

Energy absorber ABM with lanyard LB 101
and connectors AZ 002 (galvanized steel, opening 19mm)
AZ 029 (galvanized steel, plastic, opening 50mm)

2,0 m



Ref. no. **BW200/LB101/AZ003/AZ029**

Energy absorber ABM with lanyard LB 101
and connectors AZ 003 (aluminium, opening 20mm)
AZ 029 (galvanized steel, plastic, opening 50mm)

2,0 m

Ref. no. **BW200/LB101**

Energy absorber ABM with lanyard LB 101
WITHOUT CONNECTORS

1,8 m

OTHER DEVICE CONFIGURATIONS ON SPECIAL REQUEST