

Rigging equipment



COLLINOX



AMPOULE COLLINOX



BAT'INOX



AMPOULE BAT'INOX

COLLINOX^{P55}

Forged stainless steel glue-in bolt

- 10 x 70 mm

AMPOULE COLLINOX

P56

Resin glue for COLLINOX

BAT'INOX^{P57}

Forged stainless steel glue-in bolt

- 14 x 100 mm

AMPOULE BAT'INOX^{P41}

Resin glue for BAT'INOX



PAW S



PAW M



PAW L

PAW

Rigging plate

- For easy organization of the work area and for creating multiple anchor systems
- 19 mm holes allow the locking sleeves of most carabiners to pass through
- Made of aluminum: excellent strength-to-weight ratio
- Breaking strength: 36 kN
- Available in three sizes
 - PAW S (**P63 S**): small (weight 55 g)
 - PAW M (**P63 M**): medium (weight 210 g)
 - PAW L (**P63 L**): large (weight 350 g)
- Also available in black
- Certification(s): CE, NFPA 1983 General Use



SWIVEL S



SWIVEL L

SWIVEL

Swivel

- Prevents the rope from twisting when the load is turning
- Excellent performance and reliability due to maintenance-free sealed ball-bearings
- **SWIVEL S (P58 S)**:
 - designed for one-person loads
 - compact
 - breaking strength: 23 kN
 - weight: 95 g
 - Certification(s): CE
- **SWIVEL L (P58 L)**:
 - designed for two-person loads, up to three connectors can be attached to the ends
 - breaking strength: 36 kN
 - weight: 150 g
 - Certification(s): CE, NFPA 1983 General Use

HARNESSES

HELMETS

LANYARDS AND ENERGY ABSORBERS

MOBILE FALL ARRESTER

CONNECTORS

DESCENDERS

ASCENDERS

PULLEYS

ANCHORS AND ROPES

PACKS AND ACCESSORIES