



The RIG descender's multi-functional handle allows the user to control the descent and to position himself at the work station. The automatic return system on the handle limits risks in case of an involuntary action by the user.

I'D L

Self-braking descender with anti-panic function

- Designed for rescue: lacks gated attachment hole
- Multi-functional handle allows the user to:
 - unblock the rope and control the descent with the hand on the free end of the rope
 - move more easily on horizontal or low-angle terrain, thanks to the button on the handle
 - get into position without having to tie off the device
- Anti-panic function is engaged if the user pulls too strongly on the handle: brakes and stops the descent automatically
- Anti-error safety catch to reduce the risk of an accident due to incorrect installation of the device on the rope
- Pivoting cam facilitates taking up the slack in the rope. Can also be used to make a reversible haul system, and for short ascents (in conjunction with a FOOTPRO or FOOTCORD foot loop and an ASCENSION handled rope clamp)
- Lowers heavy loads up to 272 kg (only for expert users; consult the Instructions for Use for the device at www.petzl.com)
- For ropes between 11.5 and 13 mm in diameter
- Available in two colors:
 - I'D L (D200LO): red
 - I'D L (D200LN): black
- Certification(s):
 - CE EN 341 class A
 - CE EN 12841 type C
 - NFPA 1983 General Use
- Weight: 530 g

RIG

Compact self-braking descender

- Designed for rope access work (expert users only)
- Multi-functional handle allows the user to:
 - unblock the rope and control the descent with the hand on the free end of the rope
 - get into position without having to tie off the device
- The automatic return system on the handle limits risks in case of an involuntary action by the user
- Handle storage position reduces the risk of snagging when the descender is being carried on the harness
- The safety gate on the moving side plate helps prevent dropping the device and facilitates installation of the rope when passing intermediate anchors
- Pivoting cam facilitates taking up the slack in the rope. Can also be used to make a reversible haul system, and for short ascents (in conjunction with a FOOTAPE or FOOTCORD foot loop and an ASCENSION handled rope clamp)
- Lowers heavy loads up to 200 kg (only for expert users; consult the Instructions for Use for the device at www.petzl.com)
- For single ropes between 10.5 and 11.5 mm in diameter
- Available in two colors:
 - RIG (D21A): yellow
 - RIG (D21AN): black
- Certification(s):
 - CE EN 12841 type C
 - CE EN 341 class A
 - NFPA 1983 Technical Use
- Weight: 380 g



Find more about the RIG at www.petzl.com/RIG

HARNESSES

HELMETS

LANYARDS AND ENERGY ABSORBERS

MOBILE FALL ARRESTER

CONNECTORS

DESCENDERS

ASCENDERS

PULLEYS

ANCHORS AND ROPES

PACKS AND ACCESSORIES