

MOBILE FEEDING UNITS



Mobile feeding units for airlines

With duration from 120 min to 15 hours approximately. Available with one or two 50 l cylinders 300 bar or 2 or 4 steel cylinders 6 l 300 bar. They can feed one or two men via hose cuts of 10, 20, 30 or 50 m.

In the **BUSS** version it is possible to connect the trolley to an airline so that it can act as a back-up. Should the air from the main supply be interrupted, the trolley automatically switches to the cylinder pack, thus ensuring continuity of operation.

All mobile units can be used with simple **kits RL**, full face mask - demand valve - waist belt or connected to any Spasciani breathing apparatus equipped with 4Way valve.



RC 2603



RC 25002



BUSS 4603

Mobile feeding units RC

1513300CJ	RC 2603 Twin Cylinder trolley 2x6l 300 bar, duration 2 hours approx.
1514100CJ	RC 4603 Single Cylinder Trolley 4x6l 300 bar cylinders, dur. 4 hours approx.
1513700EC	RC 15002 Single Cylinder Trolley EN 144 w/o cylinder
1513800CJ	RC 25002 Twin Cylinder Trolley EN 144 w/o cylinders
932620000	RB Pressure reducer

Mobile feeding units for RL

1513600CJ	Cylinder and filter unit - 2x6l 300 bar (BUSS)
1513900CJ	Cylinder and filter unit - 4x6 l 300 bar (BUSS)
1513500EC	Filter unit - 2x50 l 200 bar (BUSS) EN144*
4049900KT	BVF/A BU 1303 breathing apparatus
	Cascade system

*w/o cylinders

Kit RL for one operator

4058000KT	Kit TR 2002 A, demand valve, waist belt
4058200KT	Kit TR 2002 BN, demand valve, waist belt

Accessories

1393000CJ	10 m 8 x 17 hose cut with connectors
1393100CJ	20 m 8 x 17 hose cut with connectors
1393300CJ	30 m 8 x 17 hose cut with connectors
1393200CJ	50 m 8 x 17 hose cut with connectors
148130000	Holding belt
1588500CJ	Demand valve A
11300000	Mask TR 2002 A

RC 2603

The mobile feeding unit **RC 2603** is fitted with two cylinders 6 l 300 bar which ensure an autonomy of approx. 120 min to one user. The trolley is fitted with release and check valves which permit the replacement of cylinder in use to extend autonomy. The reducer group is simple to operate and allows monitoring both the high and intermediate pressure. A whistle activates when the air reserve is going to finish.

RC 25002

The mobile feeding unit **RC 25002** can hold two cylinders 50 l 200 or 300 bar which ensure with the latter an autonomy of approx. 120 min to one user. This unit is designed to get maximum autonomy while keeping the system movable and handy. It can be displaced by one man only. The toolbox can hold all the accessories that make up the airline.



External alarm whistle
MP gauge
HP Gauge
Backup line connection
Release valve to replace cylinder
Hose reel 50 m



External alarm whistle
MP gauge
HP gauge
Backup line connection
Release valve to replace cylinder
Hose reel 50 m
RL accessories box

BUSS 4603

The mobile unit **BUSS 4603** is a backup system for airlines. It can be used independently with the same performances of a feeding unit or it can be connected to an airline through a filter group. In this configuration, should the air from the main supply be interrupted, the trolley automatically switches to the cylinder pack, thus ensuring continuity of operation. When the main air source is restored it switches back to normal operation. It is also possible to replace bottles during use to extend duration.

